



Slice-N-Seed RATE CHARTS

These charts are a *starting point* for finding the gauge setting for your Gandy Slice-N-Seed.

Follow this procedure when using these charts:

- 1. DETERMINE THE RATE:**
Read the product label and determine the rate to be applied. **All rates are calibrated for 1,000 square feet.**
- 2. CHECK YOUR GROUND SPEED:**
Ground speed is an important factor in determining the application rate. **All rates are calibrated for ground speed of 2.5 m.p.h.**
- 3. DETERMINE THE GAUGE SETTING:**
The term "gauge setting" refers to the numbers stamped on the gauge of the adjustable stainless steel bottom, which comes as standard equipment.

Find the chart for your product. Find your rate and gauge setting. *Set the gauge using the top of the stop as the gauge point.*

BENTGRASS

Penncross
Gauge settings:
5 10 15 20 25 30
lbs. .2 .7 1.3 2.0 3.0 4.3

Penneagle
Gauge settings:
5 10 15 20 25
lbs. .4 1.1 2.0 3.2 4.5

CENTIPEDE SEED

Prime Turf
Gauge settings:
5 10 15 20
lbs. .01 .3 0.7 1.5

MIXTURE

Athletic Pro Turf
Gauge settings:
10 15 20 25 30 35 40 45 50 55 60
lbs. .1 .2 .3 .6 .9 1.6 2.3 3.7 4.6 7.0 10.1

FESCUE

Scaldis Hard
Gauge settings:
20 25 30 35 40 45 50 55 60 65
lbs. .1 .3 .5 1.0 1.3 1.9 2.7 3.9 5.4 7.2

Overseeder II

Gauge settings:
10 15 20 25 30 35 40 45 50 55 60
lbs. .1 .2 .3 .6 1.0 1.7 2.5 3.4 5.0 6.8 9.0

RYEGRASS PERENNIAL

Pennfine
Gauge settings:
35 40 45 50 55 60 65 70 75
lbs. .4 .7 1.2 1.7 3.3 4.4 6.6 7.4 9.2

Rugby Creeping Red

Gauge settings:
20 25 30 35 40 45 50 55 60 65 70 75
lbs. .1 .2 .3 .5 .8 1.0 1.5 2.2 3.0 4.1 5.3 6.2

Del Ray

Gauge settings:
30 35 40 45 50 55 60 65 70
lbs. .6 1.1 1.5 2.3 3.2 5.0 6.7 8.6 10.6

KENTUCKY BLUEGRASS

Aspen
Gauge settings:
10 15 20 25 30 35 40 45 50 55 60
lbs. .1 .2 .4 .8 1.3 2.0 2.7 3.7 4.9 6.8 8.5

Parade

Gauge settings:
10 15 20 25 30 35 40 45 50 55
lbs. .1 .3 .6 1.2 1.9 2.8 3.8 5.3 7.0 9.0

Rugby

Gauge settings:
10 15 20 25 30 35 40 45 50 55
lbs. .1 .3 .6 1.4 1.9 3.2 4.3 6.1 7.9 10.7

Gandy Company
PO Box 528
Owatonna, MN 55060
507/451-5430